| Clair | Nutley | Carlstadt | Ridgefield | Ridgefield | Rutherford | Carlstadt | Ridgefield | Rutherford | Christadt | Ridgefield | Rutherford | Christadt | Ridgefield | Cliffside Park | Cliff


12000 24000

ISSUED FOR BID

AEB

APPD

CIVIL ENGINEERING DESIGN DRAWINGS SCCC AND DIAMOND SITES KEARNY, NEW JERSEY



Prepared for:

PENINSULA RESTORATION GROUP

0 2000 4000 FEE

CHKD: AEB DATE: 02/27/09
APPD: PWS DATE: 02/27/09

TITLE SHEET


Interim response action design sccc and diamond sites kearny, new jersey


T-01


DRAWING NO.	<u>TITLE</u>	DRAWING NO.	<u>TITLE</u>	
T-01 E-01	TITLE SHEET EXISTING CONDITIONS SITE PLAN	SM-01 SM-02	SEDIMENT MANAGEMENT PLAN SEDIMENT MANAGEMENT CROSS SECTIONS	
IRA-01 ESC-01	PROPOSED OVERALL IRA PLAN SOIL EROSION AND SEDIMENT CONTROL PLAN	SM-03 DW-01	TURBIDITY BARRIER DETAIL DEWATERING OPERATIONS PLAN	
ESC-02 SSP-01	SOIL EROSION AND SEDIMENT CONTROL DETAILS SSP BARRIER WALL PLAN	SWM-01 SWM-02	STORMWATER MANAGEMENT SYSTEM PLAN STORMWATER MANAGEMENT SYSTEM DETAILS	
SSP-02 SSP-03	SSP BARRIER WALL PROFILE SSP BARRIER WALL DETAILS	SWM-03 SWM-04	STORMWATER MANAGEMENT SYSTEM DETAILS STORMWATER MANAGEMENT SYSTEM DETAILS	
SSP-04 CBS-01	SSP BARRIER WALL GENERAL NOTES SLURRY WALL PLAN	SPA-01 SPA-02	SEPTIC TANK AND TRANSFORMER PAD LOCATION PI SEPTIC TANK REMOVAL AND BACKFILL DETAILS	_AN
CBS-02 CBS-03	SLURRY WALL PROFILE 1 OF 2 SLURRY WALL PROFILE 2 OF 2	SPA-03 MTG-01	TRANSFORMER PAD REMEDIATION DETAILS SHORELINE RESTORATION/WETLAND MITIGATION PL	ΔN
CBS-04 SD-01	SLURRY WALL DETAILS SOUTH DITCH REMEDIATION PLAN	MTG-02 MTG-03	SHORELINE RESTORATION/WETLAND MITIGATION DE	ETAILS
SD-02	SOUTH DITCH REMEDIATION PROFILES AND CROSS SECTIONS	MTG-04	SHORELINE RESTORATION/WETLAND MITIGATION CI SHORELINE RESTORATION/WETLAND MITIGATION CI	
SC-CA-01 SC-CA-02	SCCC CONSOLIDATION AREA CONSTRUCTION PLAN SCCC CONSOLIDATION AREA CROSS SECTIONS	GWT-01 GWT-02	GROUNDWATER TREATMENT FACILITY PLAN CONVEYANCE PIPE AND CONDUIT DETAILS	
SC-CA-03 DS-CA-01	SCCC CONSOLIDATION AREA DETAILS DIAMOND CONSOLIDATION AREA CONSTRUCTION PLAN	TT-01 TT-02	TEMPORARY TREATMENT SYSTEM LINE DRAWING TEMPORARY CONSTRUCTION TREATMENT SYSTEM	PROCESS AND
DS-CA-02 DS-CA-03	DIAMOND CONSOLIDATION AREA CROSS SECTIONS DIAMOND CONSOLIDATION AREA DETAILS		INSTRUMENTATION DIAGRAM	PENINSULA RESTORATION GROUP
				DENAL WAS DATE OF INT IND


ISSUE DATE:

REFERENCE: USGS 7.5 MINUTE TOPOGRAPHIC QUADRANGLES OF JERSEY CITY, AND WEEHAWKEN, NJ-NY.
AAA, NEW JERSEY AND PENNSYLVANIA ROAD MAP. 1997.












BOTTOM 1 FT. OF FABRIC EMBEDDED IN 6 INCH TRENCH TAMPED IN PLACE.











INLET SEDIMENT PROTECTION


2 STABILIZED CONSTRUCTION ACCESS DETAIL

ISSUED FOR BID

DESCRIPTION

<u>A</u> 12/22/09

REV # DATE



SOIL EROSION AND SEDIMENT CONTROL NOTES

- ALL SOIL EROSION AND SEDIMENT CONTROL PRACTICES ON THIS PLAN WILL BE CONSTRUCTED IN ACCORDANCE WITH THE "STANDARDS FOR SOIL EROSION AND SEDIMENT CONTROL IN NEW JERSEY" LAST REVISED JULY 1999
 (STANDARDS). THESE MEASURES WILL BE INSTALLED PRIOR TO ANY MAJOR SITE DISTURBANCE OR IN THEIR PROPER SEQUENCE AND MAINTAINED UNTIL PERMANENT PROTECTION IS ESTABLISHED.
- SEEDING DATES: BASED UPON THE SEED MIXTURES SPECIFIED BELOW, THE FOLLOWING SEEDING DATES ARE ACCEPTABLE TO ESTABLISH PERMANENT VEGETATIVE COVER: MARCH 1 TO OCTOBER 1. AS IDENTIFIED IN THE STANDARDS, SEED MIXTURE NUMBER 14 SHALL BE UTILIZED FOR THE ESTABLISHMENT OF VEGETATION OF THE DRAINAGE CHANNELS. ALL OTHER AREAS SHALL BE SEEDED WITH SEED MIXTURE NUMBER 17, INCLUDING PLATEAU AND SIDE SLOPE AREAS. ALTERNATE SEED MIXTURES ARE SUBJECT TO
- THE APPROVAL OF THE ENGINEER.
 SILT FENCE SHALL BE INSTALLED AROUND THE PERIMETER OF THE SITE PRIOR
 TO ANY INTRUSIVE ACTIVITIES. ALL SILT FENCE IS TO BE PROPERLY TRENCHED AND MAINTAIN UNTIL PERMANENT VEGETATIVE COVER IS ESTABLISHED. SEDIMENT RETAINED BY SILT FENCE AT THE TIME OF REMOVAL SHALL BE SPREAD ON-SITE AT A LOCATION DIRECTED BY THE ENGINEER AND RESEEDED.
- INSTALL INLET SEDIMENT/PROTECTION MEASURES FOR ALL PROPOSED INLETS AS SOON AS THEY ARE BROUGHT INTO SERVICE. STORM DRAINAGE OUTLET POINTS SHALL BE PROTECTED AS REQUIRED BEFORE THEY BECOME
- FOR ESTABLISHMENT OF A PERMANENT VEGETATIVE COVER, MULCH MATERIALS SHALL BE UN-ROTTED SALT HAY OR SMALL GRAIN STRAW APPLIED AT THE RATE OF 70-90 POUNDS PER 1000 SQUARE FEET (1.5-2.0 TONS/ACRE). ADDITIONAL REQUIRED MULCH PRACTICES ARE PRESCRIBED IN THE STANDARDS. OTHER PERMANENT REVEGETATION MEASURES, WHICH INCLUDE SITE PREPARATION, SEEDBED PREPARATION AND PERMANENT SEEDING, SHALL BE CONDUCTED IN ACCORDANCE WITH THE STANDARDS. PRIOR TO PERMANENT SEEDING, SCARIFICATION OF TOPSOIL SHALL BE LIMITED TO A MAXIMUM DEPTH OF THREE (3) INCHES TO PREVENT DISTURBANCE OF THE UNDERLYING CONTAINMENT AREA MATERIALS.
- ALL EROSION CONTROL DEVICES SHALL BE PERIODICALLY INSPECTED,
 MAINTAINED AND CORRECTED BY THE CONTRACTOR. ANY DAMAGE INCURRED BY EROSION SHALL BE RECTIFIED IMMEDIATELY.
- THE HUDSON-ESSEX-PASSAIC SOIL CONSERVATION DISTRICT WILL BE NOTIFIED IN WRITING AT LEAST 72 HOURS PRIOR TO ANY SOIL DISTURBING ACTIVITIES.
- FAX (973) 364-0784 EMAIL INFORMATION@HEPSCD.ORG.

 THE APPLICANT MUST OBTAIN A DISTRICT ISSUED REPORT-OF-COMPLIANCE
 PRIOR TO APPLYING FOR THE CERTIFICATE OF OCCUPANCY OR

 TEMPORARY CERTIFICATE OF OCCUPANCY FROM THE RESPECTIVE
 MUNICIPALITY, NJ DCA OR ANY OTHER CONTROLLING AGENCY. CONTACT
 THE DISTRICT AND GIVE ADVANCED NOTICE UPON COMPLETION OF THE RESTABILIZATION MEASURES. A PERFORMANCE DEPOSIT MAY BE POSTED WITH THE DISTRICT WHEN WINTER WEATHER OR SNOW COVER PROHIBITS THE PROPER APPLICATION OF SEED, MULCH, FERTILIZER OR HYDRO-SEED.
- PAVED ROADWAYS MUST BE KEPT CLEAN AT ALL TIMES. SOIL OR MUD THAT IS SPILLED, DROPPED, WASHED OR TRUCKED ONTO PUBLIC ROADS SHALL BE REMOVED IMMEDIATELY AND PLACED ON SITE AT A LOCATION DIRECTED BY
 - ALL DISTURBED SURFACES NOT STABILIZED WITH AGGREGATE ARE TO BE PROVIDED WITH 6 INCHES OF TOPSOIL PRIOR TO PERMANENT RE-SEEDING.
- ALL PLAN REVISIONS MUST BE SUBMITTED TO THE DISTRICT FOR PROPER 11. REVIEW AND APPROVAL.
- STABILIZED CONSTRUCTION ACCESS IS TO BE INSTALLED AT ALL SITE ENTRANCES/EXITS USING ASTM C-33 SIZE NO. 2 OR NO. 3 CRUSHED AGGREGATE TO A MINIMUM LENGTH OF 100 FEET. THE CONSTRUCTION ACCESS SHALL BE MAINTAINED THROUGHOUT THE PROJECT. ADDITIONAL STONE SHALL BE APPLIED AS CONDITIONS DEMAND.
- MAXIMUM SOIL SLOPES SHALL NOT EXCEED 2:1 UNLESS ADDITIONAL MEASURES ARE TAKEN AND APPROVED BY THE SOIL CONSERVATION DISTRICT. THESE "SPECIAL" MEASURES SHALL BE DESIGNED BY THE APPLICANT'S ENGINEER.
- THE HUDSON-ESSEX-PASSAIC SOIL CONSERVATION DISTRICT SHALL BE NOTIFIED, IN WRITING, FOR THE SALE OF ANY PORTION OF THE PROJECT OR FOR THE SALE OF INDIVIDUAL LOTS. NEW OWNERS' INFORMATION SHALL BE PROVIDED. ADDITIONAL MEASURES DEEMED NECESSARY BY DISTRICT OFFICIALS SHALL BE IMPLEMENTED AS CONDITIONS WARRANT.
- TEMPORARY DIVERSIONS, AS SHOWN ON THIS DRAWING, SHALL BE USED AS REQUIRED THROUGHOUT CONSTRUCTION TO PREVENT DIRECT DISCHARGE OF
- CONCENTRATED STORMWATER FLOW FROM THE SITE.
 DUST CONTROL MEASURES SHALL BE PERFORMED IN ACCORDANCE WITH THE


PENINSULA RESTORATION GROUP DRWN: SCC DATE: 03/24/09 CHKD: BTS DATE: 03/24/09 APPD: AEB DATE: 03/24/09


INTERIM RESPONSE ACTION DESIGN SCCC AND DIAMOND SITES KEARNY, NEW JERSEY STATE OF NEW JERSEY


SOIL EROSION AND SEDIMENT CONTROL DETAILS


24GA27961400

ROJECT NO: 09-803/80 ESC-02









- SSP WALL DESIGN USES RANKINE EARTH PRESSURES AND CONSIDERS BOTH SHORT TERM CONSTRUCTION AND FINAL SUPPORT CONDITIONS.
- SOIL PARAMETERS USED IN THE DESIGN ARE DERIVED FROM SUBSURFACE SOILS DATA PRESENTED WITHIN PROJECT INFORMATION COMPLIED AND PROVIDED BY KEY ENVIRONMENTAL.
- DESIGN USES CANTILEVERED SHEET PILING TO SUPPORT UNBALANCED EARTH AND HYDROSTATIC LOADING. THE DESIGN ALSO INCLUDES SUPPLEMENTAL STRUCTURAL COMPONENTS (BACKUP WALER AND GEOGRID REINFORCING) TO FURTHER CONTROL DEFLECTION AND ACCOUNT FOR MINOR DÍSCREPANCIES BETWEEN ESTIMATED DESIGN PARAMETERS AND VARYING FIELD CONDITIONS.
- SHEET PILE WALL ALIGNMENT SHALL BE AS NOTED ON DRAWING SSP-01 WHICH PROVIDES CALCULATED ALIGNMENT COORDINATES. ANY ADJUSTMENT TO THE PRESCRIBED ALIGNMENT SHALL BE SUBJECT TO APPROVAL BY THE ENGINEER.

MATERIALS:

- PROVIDED SHEETPILING SHALL BE NEW. AS A MINIMUM, SHEET PILING MATERIAL SHALL COMPLY WITH ASTM A328 (Fy = 39 KSI, MIN.), AND SHALL BE PRODUCED BY
- CANTILEVERED SHEETPILING SHALL PROVIDE A MIN. SECTION MODULUS OF 33.5in³/ft. USE AZ-18-700 SECTIONS MANUFACTURED BY ARCELOR MITTAL. ALTERNATE SECTIONS PROVIDING A "GREATER" SECTION MODULUS MAY BE USED PENDING THE ENGINEER'S ACCEPTANCE.
- SHEET PILING INTERLOCKS SHALL BE SEALED AS PER DRAWING DETAIL 4/SSP-03 TO CONTROL GROUNDWATER MIGRATION ACROSS THE SSP WALL.
- SHEET PILING SHALL BE COATED WITH "BITUMASTIC 300 M", OR APPROVED EQUAL, TO AN ELEVATION OF -3.00' OR BELOW (I.E., THE UPPER 13', MIN.) IF REQUIRED, SUPPLEMENTAL STRUCTURAL STEEL SHALL COMPLY WITH:
- WIDE-FLANGE "W" SHAPES ASTM A992, Fy = 50 ksi,
- "HP" SHAPES ASTM A572, Fy = 50 ksi,
- PIPE SECTIONS ASTM A53, Gr. B, Fy = 35 ksl
- MISC. PLATES AND CHANNELS ASTM A36, Fy = 36 kgl
- 6. ANCHOR BOLTS, NUTS AND WASHERS SHALL BE GALVANIZED AND COMPLY WITH THE MATERIAL REQUIREMENTS OF ASTM F1554, GR. 36.

CONCRETE:


- REINFORCING STEEL SHALL BE GRADE 60 DEFORMED BARS CONFORMING TO THE MATERIAL REQUIREMENTS OF ASTM A615. ALL REINFORCING SHALL BE EPOXY-COATED IN ACCORDANCE WITH ASTM D 3963
- CONCRETE SHALL PROVIDE A 28-DAY COMPRESSIVE STRENGTH OF 4,000 psl. CONCRETE SHALL BE DESIGNED WITH A MAXIMUM WATER/CEMENT RATIO OF 0.45, ENTRAINED AIR CONTENT OF 4 % TO 7 %, AND MINIMUM 3/4 INCH
- 3. ALL CONCRETE SHALL BE PLACED WITH A SLUMP RANGE OF 2 INCHES TO 4 INCHES. ANY OUT OF SPECIFICATION CONCRETE SHALL BE REJECTED AT THE COST OF THE CONTRACTOR. WATER MAY BE ADDED TO THE FRESH CONCRETE ONLY (1) ONE TIME WHILE ON SITE AND ONLY AT THE BEGINNING OF DISCHARGE OF THE CONCRETE

WELDING:

- ALL WELDS SHALL BE MADE BY APPROVED CERTIFIED WELDERS AND SHALL CONFORM TO THE AMERICAN WELDING SOCIETY CODE FOR BUILDINGS, AWS D1.1.
- 2. ALL WELDED CONNECTIONS SHALL BE MADE WITH E70XX ELECTRODES.

GENERAL CONSTRUCTION PROCEDURES

- 1. CONSTRUCTION SHALL COMPLY WITH ALL APPLICABLE REQUIREMENTS OF OSHA CFR 29. PART 1926.
- COMPLETE 2' DEEP EXCAVATION ALONG THE ALIGNMENT OF THE SHEET PILING SSP WALL AS REQUIRED TO CLEAR THE DRIVELINE OF OBSTRUCTIONS.
- DRIVE SHEET PILING ALONG THE DESIGN ALIGNMENT TO THE TOE DEPTHS SPECIFIED ON THESE DRAWINGS. THE SPECIFIED TOE DEPTH IS A MINIMUM INSTALLATION DEPTH.
- PLACE, GRADE AND COMPACT FILL BEHIND THE SSP WALL IN ACCORDANCE WITH PROJECT SPECIFICATIONS AND AS FOLLOWS:
- USE STRUCTURAL FILL FOR THE INITIAL CONSTRUCTION / LEVELING LIFT TO PROVIDE A UNIFORM, LEVEL BASE FOR THE CAPILLARY BREAK SYSTEM. THE CONSTRUCTION / LEVELING LIFT SHALL BE COMPACTED TO A PERFORMANCE-VERIFIED IN PLACE DENSITY.
- PLACE AND COMPACT SUBSEQUENT LIFTS OF STRUCTURAL FILL ABOVE THE CAPILLARY BREAK SYSTEM TO 95% OF THE MAX. MODIFIED PROCTOR DENSITY (MPD) (ASTM D1557). IN PLACE FILL SHALL PROVIDE A FIRM COMPACTED BASE FOR CONSTRUCTION OF THE CONCRETE WALER.
- 5. INSTALL GEO-GRID REINFORCEMENT AS SHOWN ON DRAWING SHEET SSP-03.
- CONSTRUCT AND INSTALL CONCRETE WALER AS SHOWN, AND TO THE DIMENSIONS NOTED (AS MIN.). ON DRAWING SSP-03.
- PLACE AND COMPACT ADDITIONAL STRUCTURAL FILL TO PROVIDE A STABLE BEARING GRADE FLUSH WITH THE TOP OF THE CONCRETE WALER (ELEV. +8.0).
- USE CRANE MATS OR OTHER FORMS OF DONNAGE TO LIMIT CONSTRUCTION SURCHARGE LOADS BEHIND THE SSP WALL TO A MAX. OF 500 psf DURING DREDGING
- COMPLETE EXCAVATION TO THE SPECIFIED DREDGE LIMITS.
 BACKFILL THE DREDGE AREA ACCORDING TO THE PROJECT REQUIREMENTS AND MINIMUM SPECIFIED FINAL GEOMETRY WITHIN 48 HOURS. COMPLETING THE EXCAVATION TO THE SPECIFIED LIMITS. BACKFILL SHALL BE PLACED TO FULLY CONTACT THE OUTBOARD FACE OF THE SSP WALL AND RESTORE THE PRE-EXCAVATION PASSIVE RESISTANCE.
- 11. THE ENGINEER SHALL BE NOTIFIED IMMEDIATELY IF CONDITIONS ENCOUNTERED IN THE FIELD VARY TO ANY SIGNIFICANT DEGREE FROM THOSE CONSIDERED AND REPRESENTED IN THIS DESIGN AND/OR IF EXCESSIVE MOVEMENT OF THE SSP WALL SYSTEM (> 2") IS NOTED DURING CONSTRUCTION.





GLYNN GEOTECHNICAL ENGINEERING 415 S. TRANSIT STREET LOCKPORT, NEW YORK 14094 www.glynigroup.com VOICE (716) 625 - 6993 / FAX (716) 625 - 6983

PENINSULA RESTORATION GROUP


DRWN: SCC	DATE: 06/16/09
CHKD: AEB	DATE: 08/16/09
APPD: AEB	DATE: 06/16/09
SCALE:	AS SHOWN



INTERIM RESPONSE ACTION DESIGN SCCC AND DIAMOND SITES KEARNY, NEW JERSEY

SSP BARRIER WALL GENERAL NOTES

ROJECT NO: 09-803/804 SSP-04





ISSUE DATE: SIGNATURE


DATE

PLAN PREPARER: ALAN E. BRIGGS PROFESSIONAL ENGINEER N.J. LICENSE

STATE OF NEW JERSEY
CERTIFICATE OF AUTHORIZATION TO OFFER ENGINEERING SERVICES 24GA27961400







LEGEND

FILL

MEADOWMAT

SAND

VARVED CLAY


PROPOSED TOP OF SLURRY WALL

PROPOSED BOTTOM OF SLURRY WALL

EXISTING GROUND SURFACE

PROPOSED TOP OF WORKING PLATFORM

FINAL GRADE



PENINSULA RESTORATION GROUP

DRWN: DJB DATE: 05/14/09
CHCD: DF DATE: 05/14/09
APPD: AEB DATE: 05/14/09
AS SACKIN PROPOSED TOP OF SLURRY WALL AS SHOWN HEREIN REPRESENTS A MINIMUM ELEVATION FOR CONSTRUCTION PURPOSES. CONTRACTOR MAY
INCREMENTALLY "STEP" THE ADJOINING SLURRY WALL PANELS TO ACHEVE THE MINIMUM ELEVATION, SUBJECT TO APPROVAL BY THE
ENGINEER.
 UTILITY LOCATIONS AND DEPTHS BELOW GROUND SURFACE ARE APPROXIMATE AND ARE PROVIDED FOR INFORMATIONAL PURPOSES ONLY.
CONTRACTOR SHALL VERIFY UTILITY LOCATIONS AND DEPTHS BELOW GROUND SURFACE DURING THE WORK.
 BOTTOM OF SLURRY WALL SHALL EXTEND A MIN OF 3" INTO THE VARVED CLAY LAYER. PLAN PREPARER: ALAN E. BRUGGS PROFESSIONAL ENGINEER N.J. LICENSE NUMBER: 24GE03878500

REFERENCE:

AEB <u>A</u> 12/18/09 ISSUED FOR BID REV # DATE DESCRIPTION APPD

KEY ENVIRONMENTAL, INC. 200 THIRD AVENUE CARNEGIE, PA 15106 SIGNATURE


ISSUE DATE:

CERTIFICATE OF AUTHORIZATION TO OFFER ENGINEERING SERVICES DATE 24GA27961400

INTERIM RESPONSE ACTION DESIGN SCCC AND DIAMOND SITES KEARNY, NEW JERSEY

SLURRY WALL PROFILE 1 OF 2

PROJECT NO: 09-803/80 CBS-02



LEGEND

FILL MEADOWMAT SAND VARVED CLAY PROPOSED TOP OF SLURRY WALL PROPOSED BOTTOM OF SLURRY WALL EXISTING GROUND SURFACE

PROPOSED TOP OF WORKING PLATFORM



PENINSULA RESTORATION GROUP

DRWN: DJB DATE: 05/14/09
CHCD: DF DATE: 05/14/09
APPD: AEB DATE: 05/14/09
APPD: AEB DATE: 05/14/09
AE SAMWEN

INCORPORATED

INTERIM RESPONSE ACTION DESIGN SCCC AND DIAMOND SITES KEARNY, NEW JERSEY

SLURRY WALL PROFILE 2 OF 2

ROJECT NO: 09-803/80 CBS-03

LC.	TEC.	
w	123	

PROPOSED TOP OF SLURRY WALL AS SHOWN HEREIN REPRESENTS A MINIMUM ELEVATION FOR CONSTRUCTION PURPOSES. CONTRACTOR MAY
INCREMENTALLY "STEP" THE ADJORNING SLURRY WALL PANELS TO ACHIEVE THE MINIMUM ELEVATION, SUBJECT TO APPROVAL BY THE
ENGINEER.
 UTILITY LOCATIONS AND DEPTHS BELOW GROUND SURFACE ARE APPROXIMATE AND ARE PROVIDED FOR INFORMATIONAL PURPOSES ONLY.
CONTRACTOR SHALL VERIFY UTILITY LOCATIONS AND DEPTHS BELOW GROUND SURFACE DURING THE WORK.
 BOTTOM OF SLURRY WALL SHALL EXTEND A MIN OF 3" INTO THE VARVED CLAY LAYER.

REFERENCE: 101/28/10 REVISED DIAMETER OF EXISTING WATER LINE. AEB AEB APPD

<u>A</u> 12/22/09

REV # DATE

ISSUED FOR BID

DESCRIPTION

KEY ENVIRONMENTAL, INC. 200 THIRD AVENUE CARNEGIE, PA 15105

ISSUE DATE:


SIGNATURE DATE


PLAN PREPAREN.


ALAN E. BRIGGS PROFESSIONAL ENGINEER


N.J. LICENSE NUMBER: 24GE03878500


CERTIFICATE OF AUTHORIZATION TO OFFER ENGINEERING SERVICES 24GA27961400


























CROSS SECTION B-B' CROSS SECTION A-A' -PROPOSED STEEL **PROPOSED** PROPOSED STEEL -MEAN HIGH SHEET PILE WALL EXISTING CONCRETE SLURRY WALL SHEET PILE WALL WATER LINE -MEAN HIGH STRUCTURE (+3.38)WATER LINE -EL. 10.0 AREA OF (+3.38)EXISTING 20 20 - 20 WOOD EL. 10.0 Elevation Elevation -PILES 10 10 10 (APPROX.) -10-10-10PROPOSED -20 --20PROPOSED LIMIT OF 3' SEDIMENT 3' SEDIMENT LIMIT OF **SEDIMENT** REMOVAL DEPTH -REMOVAL DEPTH SEDIMENT REMOVAL (TYP.) PROPOSED (TYP.) REMOVAL SLURRY WALL: CROSS SECTION D-D'CROSS SECTION C-C'PROPOSED STEEL PROPOSED SLURRY SHEET PILE WALL MEAN HIGH-WALL WATER LINE -MEAN HIGH WATER LINE (+3.38)PROPOSED SLURRY CONSOLIDATION WALL (+3.38)-EL. 10.0 **AREA** 20 PROPOSED STEEL EL. 10.0 SHEET PILE WALL 10 10 10 Elevation 0 -10-10-10**PROPOSED** LIMIT OF Δ PROPOSED ¹ -20-20SEDIMENT 3' SEDIMENT — LIMIT OF 30 60 REMOVAL REMOVAL DEPTH **SEDIMENT** FEET -30-30REMOVAL (TYP.) 3' SEDIMENT -30 60 REMOVAL DEPTH (TYP.) FEET **LEGEND** NOTE: 1. TIDAL ELEVATION DATA CALCULATIONS WERE PROVIDED BY GEOD PROPOSED LIMIT OF RIVER SEDIMENT EXCAVATION CORPORATION DERIVED BY UTILIZING INFORMATION FOR TIDAL PENINSULA RESTORATION GROUP STATIONS 853-0696 AND 853-0772 USING THE 1983-2001 TIDAL EPOCH AND ARE REFERENCED TO THE NATIONAL GEODETIC VERTICAL EXISTING GROUND SURFACE DATUM OF 1929 (NGVD 1929). DRWN: SCC DATE: 03/26/09 CHKD: MJH DATE: 03/26/09 TOP OF WORKING PLATFORM FOR APPD: DF DATE: 03/26/09 SLURRY WALL CONSTRUCTION PLAN PREPARER: ALAN E. BRIGGS PROFESSIONAL ENGINEER N.J. LICENSE NUMBER: 24GE03878500 (EL. +8 MSL) INTERIM RESPONSE ACTION DESIGN SCCC AND DIAMOND SITES KEARNY, NEW JERSEY EL=3.38 MEAN HIGH WATER ISSUE DATE: STATE OF NEW JERSEY REFERENCE: CERTIFICATE OF AUTHORIZATION TO OFFER ENGINEERING SERVICES PROJECT NO: 09803/804 KEY ENVIRONMENTAL, INC. 200 THIRD AVENUE CARNEGIE, PA 15106 DATE SIGNATURE 12/22/09 ISSUED FOR BID AEB SEDIMENT MANAGEMENT

REV # DATE


DESCRIPTION


APPD

SM-02

CROSS SECTIONS

24GA27961400





CANDIDATE CONSTRUCTION/DEWATERING SEQUENCE FOR SCCC SITE (CONFORMING METHODS FOR DIAMOND SITE INCLUDE ITEMS 9 THROUGH 22)

- INSTALL DEWATERING SUMPS PER DETAIL AT LOCATIONS (1)(2)(3) TO FACILITATE DEWATERING OF WEST AND EAST LAGOONS.
- PUMP WATER TO FRAC TANK(S) FOR SUBSEQUENT TREATMENT IN NJPDES-PERMITTED AND TREATMENT WORK AUTHORIZATION-APPROVED PACKAGE PLANT.
- BLOCK SOUTH DITCH INFLOW AS NECESSARY. DEWATER SOUTH DITCH WITH DEWATERING SUMP (4) AND PUMP SOUTH DITCH WATER TO FRAC TANK(S) AS ABOVE.
- COMMENCE CONSOLIDATION OF SOUTH DITCH SOFT SOIL IN WEST LAGOON 1
- RECOVER DECANTED SOUTH DITCH SOFT SOIL WATER FROM EAST LAGOON SUMPS AS NECESSARY.
- TREAT SUPERNATANT FROM SOUTH DITCH SOFT SOIL CONSOLIDATION AREA (WEST LAGOON) AS ABOVE.
- COVER CONSOLIDATED SOUTH DITCH SOFT SOIL OR EMPLOY DUST CONTROL AS NECESSARY.
- CONSTRUCT EARTHEN DAM AT LOCATION [2] TO SEPARATE BACKFILLED WEST LAGOON AND EMPTY EAST LAGOON.
- CONSTRUCT CONTAINMENT BERM AROUND CONSOLIDATION AREA PERIMETER AND COMMENCE SLURRY WALL CONSTRUCTION ON SCCC AND/OR SEABOARD SITES AND CONSOLIDATE SPOILS IN EAST LAGOON 3.
- 10. RECOVER SUPERNATANT FROM SLURRY WALL SPOILS IN EAST LAGOON USING SUMP AND PUMP AT LOCATION (3)
- 11. IF SPOILS VOLUME EXCEEDS AVAILABLE AIR SPACE IN EAST LAGOON, RECOVER SUPERNATANT FROM LOW SPOT INSIDE PERIMETER BERM 4 AND 5 AND STORE IN FRAC TANK(S).
- 12. TREAT SUPERNATANT FROM SLURRY WALL SPOIL CONSOLIDATION AREA (EAST LAGOON AND SCCC CONSOLIDATION AREA) AS ABOVE.
- 13. GRADE SPOILS IN CONSOLIDATION AREA AS NECESSARY IN VIEW OF ANTICIPATED FINAL GRADES.
- 14. COVER CONSOLIDATED SLURRY SPOILS OR EMPLOY DUST CONTROL AS NECESSARY.
- 15. COMMENCE EXCAVATION OF RIVER SEDIMENTS FROM SCCC RIVER FRONTAGE (AND PORTION OF DIAMOND RIVER FRONTAGE) AND CONVEY TO SCCC CONSOLIDATION AREA.
- 16. COLLECT SUPERNATANT FROM RIVER SEDIMENT USING PUMP AND SUMP AT LOCATION (5). STORE IN FRAC TANKS.

 17. TREAT SUPERNATANT FROM RIVER SEDIMENT CONSOLIDATION
- AREA 5 (SCCC CONSOLIDATION AREA) AS ABOVE.
- 18. GRADE CONSOLIDATED RIVER SEDIMENTS TO ACCOMMODATE FINAL GRADE.
- 19. COVER CONSOLIDATED RIVER SEDIMENTS OR EMPLOY DUST CONTROLS AS NECESSARY.
- 20. COMPLETE EXCAVATION OF HYDRAULIC CONTROL AND DNAPL RECOVERY SYSTEM TRENCHES 6 AND DEWATER USING SUMP
- AND PUMP (6) PER DETAIL.

 21. CONSOLIDATE EXCESS TRENCH SPOILS IN CONSOLIDATION AREA (SCCC OR DIAMOND).
- 22. MANAGE WATER IN TRENCHES AND CONVEY EXCESS WATER FROM TRENCH DEWATERING OPERATIONS TO FRAC TANK(S) AS NECESSARY AND TREAT AS ABOVE.

NOTES:

1. WATER TO BE TREATED IN TEMPORARY NJPDES-PERMITTED TREATMENT WORKS (SOLIDS, METALS, ORGANICS REMOVAL).

ISSUED FOR BID 12/22/09 REV # DATE DESCRIPTION APPD

REFERENCE:

1. EXISTING GROUND SURFACE CONTOURS PER AIR SURVEY, DULLES, VIRGINIA, APRIL 14, 2001, HORIZONTAL REFERENCE: NEW JERSEY STATE PLANE COORDINATES (NAD AEB 2. PROPERT

ALAN E. BRIGGS PROFESSIONAL ENGINEER N.J. LICENSE NUMBER: 24GE03878500 ISSUE DATE: KEY ENVIRONMENTAL, INC. 200 THIRD AVENUE CARNEGIE, PA 15106 SIGNATURE

STATE OF NEW JERSEY CERTIFICATE OF AUTHORIZATION TO OFFER ENGINEERING SERVICES DATE 24GA27961400


DRWN: WAA DATE: 04/20/09 CHKD: RJH DATE: 04/20/09 APPD: AEB DATE: 04/20/09


PENINSULA RESTORATION GROUP


INTERIM RESPONSE ACTION DESIGN SCCC AND DIAMOND SITES KEARNY, NEW JERSEY


DEWATERING OPERATIONS PLAN


ROJECT NO: 09-803/804 DW-01











DIAMOND CONSOLIDATION AREA


VEGETATED CHANNEL

CHANNEL C-4D


	CHANNEL SCHEDULE									
CHANNEL	zL	z _R	WIDTH W	SLOPE So (FT./FT.)	TOTAL DEPTH D	LINING		THICKNESS t	LOCATION	
			(FT.)	(11.711.)	(FT.)	TEMP	PERM	(IN.)		
C-1	3	2	1	.007	1.1	HVECMB	G	ı	EAST SIDE OF SCCC SITE CONSOLIDATION AREA	
C-2	3	2	1	.012	1.0	HVECMB	G	ı	EAST SIDE OF SCCC SITE CONSOLIDATION AREA	
C-3A	3	3	1	.005	1.3	HVECMB	G	ı	NORTH SIDE OF SCCC SITE CONSOLIDATION AREA	
C-3B	3	3	1	.008	1.5	HVECMB	G	ı	NORTH SIDE OF SCCC SITE CONSOLIDATION AREA	
C-4A	3	3	2	.007	1.4	HVECMB	G	ı	NORTH SIDE OF DIAMOND SITE CONSOLIDATION AREA	
C-4B	3	3	2	.004	1.9	HVECMB	G	_	NORTH SIDE OF DIAMOND SITE CONSOLIDATION AREA	
C-4C	3	3	2	.003	2.2	HVECMB	G	_	NORTH SIDE OF DIAMOND SITE CONSOLIDATION AREA	
C-4D	3	3	2 TO 15	.001	2.6 TO 0	HVECMB	G	-	EAST SIDE OF DIAMOND SITE CONSOLIDATION AREA	


HVECMB = HIGH VELOCITY EROSION CONTROL MULCH BLANKET G = GRASS

CHANNEL DETAIL AND SCHEDULE N.T.S.



	RIPRAP APRON SCHEDULE								
	PIPE	RIP	RAP		APF	RON			
OUTLET NO.	DIA Wo (IN)	D50 THICK. SIZE Rt. (R IN) (IN)		LENGTH L (FT)	INITIAL WIDTH Aiw (FT)	TERMINAL WIDTH Atw (FT)	INV. EL. (FT)		
1	39.3	6	12	16.5	10	26.5	-1.8		
2	26.2	13.2	26.4	26.4	6.5	33.0	+0.0		
- 3	50.5	12.7	25.4	.30	12	42	-3.2		





SSP BARRIER WALL PENETRATION DETAIL SWM-03

NOTE: CONTRACTOR TO PROVIDE SHOP DRAWINGS/SUBMITTAL DEPICTING MEANS OF PREFABRICATING SHEET PILE PENETRATION/STEEL SLEEVE.

	4	1
(SV	VM-	03/

RIPRAP APRON DETAIL AND SCHEDULE N.T.S.

					PLAN PREPARER: ALAN E. BRIGGS PROFESSIONAL ENGINEER N.J. LICENSE NUMBER: 24GE03878500
			REFERENCE:] :
01/28/10	ADDED CHECK VALVE FOR OUTLET 001	AEB			
12/22/09	ISSUED FOR BID	AEB		KEY ENVIRONMENTAL, INC. 200 THIRD AVENUE	SIGNATURE DATE
¥ DATE	DESCRIPTION	APPD		CARNEGIE, PA 15106	







INTERIM RESPONSE ACTION DESIGN SCCC AND DIAMOND SITES KEARNY, NEW JERSEY

STORMWATER MANAGEMENT SYSTEM DETAILS

PROJECT NO: 09-803/804 SWM-03





	AN'	TICIPATED TAN	IK DIMENSI	ONS (SEE NO	OTE 5)	
TANK NUMBER	NUMBER OF TANKS	DIAMETER (FT.)	WIDTH (FT.)	LENGTH (FT.)	HEIGHT OF TANK (FT.)	DEPTH BGS (FT.)
ST-1	1 (ASSUMED)	NA	4	8	3	UNK
ST-1A	1 (ASSUMED)	NA	UNK	UNK	UNK	UNK
ST-1B	1	NA	4	4	5	0.9 (APPROX.)
ST-2	1 (ASSUMED)	NA	4	6	3	UNK
ST-3	1	NA	6	12	7	1
ST-4	1 (ASSUMED)	NA	4	6	3	UNK
ST-5	1	NA	8	8	6.3	0.8
ST-6	1	NA	3.5	4	4.7	0.3
ST-7	1	NA	5	7	4	0.3
ST-8	2	5	NA	NA	5	0.3
31-8	2	5	NA	NA	5	0.2

BGS - BELOW GROUND SURFACE

UNK - UNKNOWN NA - NOT APPLICABLE

PROPERTY BOUNDARY
LAGOON/STREAM
× × FENCE LINE
GUARD RAIL
C TREE/BRUSH AREA
GRAVEL/CONCRETE
++++++++++++++++++++++++++++++++++++++
UNDERGROUND TUNNEL
EXISTING BUILDING/STRUCTURE
FORMER BUILDING/STRUCTURE
UTILITY POLE

ISSUE DATE:

KEY ENVIRONMENTAL, INC. 200 THIRD AVENUE CARNEGIE, PA 15106

1. ALL SANITARY SEWER LINE LOCATIONS APPROXIMATE (AS-BUILTS NOT AVAILABLE).

SANITARY SEWER LINE DISCHARGE POINTS INFERRED (AS-BUILTS NOT AVAILABLE). ACTUAL CONFIGURATION OF TANKS AT BUILDING 1 UNKNOWN. TANKS MAY NOT EXIST AT LOCATIONS ST-1 AND ST-1A. TANK ST-1B MAY BE A JUNCTION BOX. ALL UTILITY LINE LOCATIONS ARE APPROXIMATE BASED ON BEST AVAILABLE INFORMATION.

TANK DIMENSIONS SHOWN WERE BASED ON HISTORICAL RECORDS AND THUS ARE APPROXIMATE.

Δ				REFERENCE:
Δ				1. EXISTING GROUND SURFACE CONTOURS PER AIR SURVEY, DULLES, VIRGINIA, APRIL 14, 2001. HORIZONTAL REFERENCE: NEW JERSEY STATE PLANE COORDINATES (NAD 1927). VERTICAL REFERENCE:NATIONAL GEODETIC VERTICAL DATUM (NGVD 1929).
◬	12/22/09	ISSUED FOR BID	AEB	2. PROPERTY BOUNDARY SHOWN HEREON FROM SHEET 1 OF 1 TITLED "SURVEY OF PROPERTY, TAX LOTS 32.02, 46, 47 & 47R, BLOCK 287, TAX LOTS 48, 49, 50, 51, AND 52R, BLOCK 287, TOWN OF KEARNY, HUDSON COUNTY, NEW JERSEY," DATED JULY 1, 2009 (REVISION 2: JULY 29, 2009), PREPARED BY DYKSTRA ASSOCIATES, I
EV#	DATE	DESCRIPTION	APPD	AND JZI, BLOCK ZDI, TOWN OF REMINE, HOUSEN COUNTY, NEW VENSET, WHILD BOLL 1, 2008 (REMINER 2, 2008), FREFARED BY DIRATIN ASSOCIATES,

PLAN PREPARER: ALAN E. BRIGGS PROFESSIONAL ENGINEER N.J. LICENSE NUMBER: 24GE03878500 DATE SIGNATURE

ST−1B **■**

ST-1A 🗆

SURFACE COVER (PREVIOUSLY INSTALLED) INTERIM REMEDIAL MEASURE AREA GEOMEMBRANE/AGGREGATE SURFACE COVER (PREVIOUSLY INSTALLED)

INTERIM REMEDIAL MEASURE AREA ASPHALT SURFACE COVER (PREVIOUSLY INSTALLED)

INTERIM REMEDIAL MEASURE AREA SOIL

SUSPECTED SEPTIC TANK LOCATION (~1.5 - 2 TIMES ACTUAL SIZE)

EXISTING OVERHEAD POWER LINE

EXISTING SANITARY SEWER (ASSUMED LOCATION)

TRANSFORMER PAD AND TRANSFORMER

EXISTING STORM SEWER EXISTING WATER LINE EXISTING GAS LINE

> APPD: AEB DATE: 04/15/09

150

PENINSULA RESTORATION GROUP

INTERIM RESPONSE ACTION DESIGN SCCC AND DIAMOND SITES KEARNY, NEW JERSEY

SEPTIC TANK AND TRANSFORMER PAD LOCATION PLAN

PROJECT NO:09-803/804 SPA-01

300

FEET

7_				REFERENCE:
7				1. EXISTING GROUND SURFACE CONTOURS PER AIR SURVEY, DULLES, VIRGINIA, APRIL 14, 2001. HORIZONTAL REFERENCE: NEW JERSEY STATE PLANE COORDINATES (NAD 1927). VERTICAL REFERENCE-NATIONAL GEODETIC VERTICAL DATUM (NGVD 1929).
7	12/22/09	ISSUED FOR BID	AEB	2. PROPERTY BOUNDARY SHOWN HEREON FROM SHEET 1 OF 1 TITLED "SURVEY OF PROPERTY, TAX LOTS 32.02, 46, 47 & 47R, BLOCK 287, TAX LOTS 48, 49, 50, 51, 5 AND 52R, BLOCK 287, TOWN OF KEARNY, HUDSON COUNTY, NEW JERSEY," DATED JULY 1, 2009 (REVISION 2: JULY 29, 2009), PREPARED BY DYKSTRA ASSOCIATES, PC
, 4	DATE	DECODIDATION	4000	AND 32K, BEOCK 287, 10MM OF REALMY, HOUSEN COUNTY, NEW BERSEY, DATED BOLT 1, 2009 (REVISION 2. BOLT 29, 2009), FREFARED BY DIKSTON ASSOCIATES, FC

STATE OF NEW JERSEY CERTIFICATE OF AUTHORIZATION TO OFFER ENGINEERING SERVICES 24GA27961400

PHOTOGRAPHS OF REPRESENTATIVE EXISTING SURFACE COMPLETIONS — SEPTIC TANKS



BUILDING 1. EFFLUENT LINE TO SUSPECTED TANK ST-1A.



NORTHEAST CORNER OF BUILDING 1. TANK OR JUNCTION BOX ST-1B



TYPICAL BLOCK/PLATE SURFACE COMPLETION, TANK ST-3




TYPICAL BLOCK/PLATE SURFACE COMPLETION, TANK ST-5





TYPICAL MANHOLE SURFACE



TYPICAL MANHOLE SURFACE COMPLETION, TANK ST-8







SEPTIC TANK REMOVAL DETAIL N.T.S

CONSTRUCTION SEQUENCE FOR REMOVAL OF SEPTIC TANKS

- 1. FIELD LOCATE THE SEPTIC TANKS AND MARK THE TANK CORNERS, ACCESS PORTS, AND INFLUENT AND EFFLUENT LINE LOCATIONS.
- 2. COMPLETE EXCAVATION AS NECESSARY TO DETERMINE IF TANKS ST-1, ST-1A, ST-2, AND ST-4 EXIST (SEE DRAWING SPA-01). PLACE EXCAVATED SOILS IN INDIVIDUAL STOCKPILES WITH A LINER, BERM/BALES, AND COVER PENDING REPLACEMENT IN THE EXCAVATION. CONVEY CONCRETE AND ASPHALT RUBBLE TO THE SCCC CONSOLIDATION AREA.
- CONSULIDATION AREA.

 3. IF ANY OF THE PRECEDING TANKS (ST-1, ST-1A, ST-2, OR ST-4) DO NOT EXIST, REPLACE CONCRETE OR ASPHALT PAVING OR OTHER SURFACE COVER MATERIAL IN KIND.

 4. IF TANKS ARE FOUND AT LOCATIONS ST-1, ST-1A, ST-2, AND ST-4, OBTAIN LIQUID AND SOLID PHASE SAMPLES FROM THE TANK. ANALYZE SAMPLES FOR TAL METALS, TCL VOLATILES AND SEMIVOLATILES, HEXAVALENT CHROMIUM, DIOXINS/FURANS, TCLP VOLATILES, TCLP SEMIVOLATILES, AND TCLP METALS.
- COVER EXCAVATED TANK LOCATIONS (ST-1, ST-1A, ST-2, AND ST-4) TO PREVENT RUNOFF, RUNON, AND
- INFILTRATION WHILE SAMPLE ANALYSIS IS PENDING (IF APPLICABLE).

 CONSTRUCT TANK DECONTAMINATION AREA WITH LINER, BERM AND SUMP FOR COLLECTION OF WASH WATER.
- 6. CONSTRUCT TANK DECONTAMINATION AREA WITH LINER, BERM AND SUMP FOR COLLECTION OF WASH WATER.

 7. REMOVE VEGETATION AND PLANTER MATERIAL (TIES, MULCH AND SOIL) FROM VICINITY OF SEPTIC TANK ST—1A IF IT IS PRESENT (TO BE REPLACED IN KIND).

 8. CUT PAVING MATERIAL, REMOVE CONCRETE BLOCK RISER STRUCTURE AS NECESSARY AND REMOVE ASPHALT OR CONCRETE PAVING. CONVEY RUBBLE TO THE SCCC CONSOLIDATION AREA.

 9. REMOVE OVERBURDEN FROM SEPTIC TANK AND STOCKPILE ADJACENT TO THE EXCAVATION WITH LINER,
- BALES/BERM, AND COVER.
- 10. REMOVE SEPTIC TANK MANHOLE COVER(S), TIE DOWNS (IF PRESENT), AND SEPTIC TANK CAP AND CONVEY TO THE DECONTAMINATION AREA FOR PRESSURE WASHING.
- 11. PUMP OUT SEPTIC TANK LIQUIDS. CONNECT PUMP TO INFLUENT/EFFLUENT LINES AND PUMP OUT CONTENTS. CUT OFF DOWNCOMER/TEE ON INFLUENT/EFFLUENT LINES.

 12. CONVEY ALL LIQUIDS FOR OFFSITE TREATMENT AND/OR DISPOSAL IN ACCORDANCE WITH NJDEP, EPA, AND
- DOT REQUIREMENTS, INCLUDING REQUISITE MANIFESTING (ANALYTICAL DATA TO BE PROVIDED TO
- 13. REMOVE SEPTIC TANK SOLIDS WITH VACUUM TRUCK OR EQUIVALENT AND CONVEY FOR OFFSITE TREATMENT AND/OR DISPOSAL IN ACCORDANCE WITH VACUUM IRUCK OR EQUIVALENT AND CONVEY FOR OFFSITE TREATMENT AND/OR DISPOSAL IN ACCORDANCE WITH NJDEP, EPA, AND DOT REQUIREMENTS, INCLUDING REQUISITE MANIFESTING (ANALYTICAL DATA TO BE PROVIDED TO CONTRACTOR).

 14. OVEREXCAVATE THE TANK AND STOCKPILE THE SOILS WITH LINER, BERMS/BALES, AND COVER ADJACENT TO THE EXCAVATION. TAKE CARE NOT TO BREAK INFLUENT AND EFFLUENT LINES.
- 15. CUT AND PLUG OR CAP INFLUENT AND EFFLUENT LINES ON THE OUTSIDE OF THE TANK.
- 16. REMOVE THE TANK AND PLACE IN THE DECONTAMINATION AREA FOR PRESSURE WASHING.
 17. PRESSURE WASH THE TANK AND THE COVER. CONVEY WASH WATER TO THE SCCC LAGOON FOR
- SUBSEQUENT MANAGEMENT BY OTHERS.
- 18. OBTAIN ONE (1) CONCRETE CHIP SAMPLE FROM BELOW APPARENT HIGH WATER LINE OF TANK INTERIOR OR FROM TANK BOTTOM AND ANALYZE SAMPLES FOR TAL METALS, TCL VOLATILES AND SEMIVOLATILES, HEXAVALENT CHROMIUM, DIOXINS/FURANS, TCLP VOLATILES, TCLP SEMIVOLATILES, AND TCLP METALS. STAGE TANKS ON LINERS AND COVER PENDING SUBSEQUENT MANAGEMENT.
- 19. OBTAIN FOUR SIDEWALL SAMPLES AND ONE BOTTOM SAMPLE FROM EXCAVATION (TAL METALS, PCBS, TCL
- VOLATILES AND SEMIVOLATILES, AND HEXAVALENT CHROMIUM ANALYSIS).

 20. BACKFILL THE EXCAVATION WITH A MINIMUM OF 2 FEET OF STRUCTURAL FILL MATERIAL. BACKFILL ABOVE STRUCTURAL FILL WITH STOCKPILED SOILS. BACKFILL REMAINING SPACE WITH STRUCTURAL FILL. PLACE 6 INCH CAPILLARY BREAK SUBGRADE AND REPLACE PAVING OR SURFACE COVER MATERIAL IN KIND.
- 21. MANAGE CONCRETE TANKS IN ACCORDANCE WITH NJDEP GUIDANCE AND APPLICABLE STATE AND LOCAL REQUIREMENTS. PRIMARY GUIDANCE FOR CONCRETE TANK MANAGEMENT IS OUTLINED IN THE NJDEP SITE REMEDIATION AND MANAGEMENT PROGRAM'S "GUIDANCE FOR THE SAMPLING AND ANALYSIS OF CONCRETE DESIGNATED FOR RECYCLING" DATED FEBRUARY 2009.

1. REFER TO SPA-01 FOR LOCATIONS AND APPROXIMATE LOCATIONS OF SEPTIC TANKS AND LINES.

REFERENCE: ISSUED FOR BID AEB REV # DATE DESCRIPTION APPD

KEY ENVIRONMENTAL, INC. 200 THIRD AVENUE CARNEGIE, PA 15106

ISSUE DATE:

PLAN PREPARER: ALAN E. BRIGGS PROFESSIONAL ENGINEER N.J. LICENSE NUMBER: 24GE03878500

SIGNATURE DATE

CERTIFICATE OF AUTHORIZATION TO OFFER ENGINEERING SERVICES 24GA27961400


DRWN: SCC DATE: 04/05/09 CHKD: GWB DATE: 04/05/09 APPD: AEB DATE: 04/05/09

PENINSULA RESTORATION GROUP

INTERIM RESPONSE ACTION DESIGN SCCC AND DIAMOND SITES KEARNY, NEW JERSEY

SEPTIC TANK REMOVAL AND BACKFILL DETAILS

PROJECT NO: 09-803/804 SPA-02



CONSTRUCTION SEQUENCE

- VERIFY THAT THE TRANSFORMER AND ALL CONDUIT HAS BEEN DISCONNECTED FROM POWER SOURCE.
- 2. CLEAR AND GRUB VOLUNTEER VEGETATION FOR DISPOSAL AT PERMITTED OFF—SITE SOLID WASTE DISPOSAL FACILITY.
- 3. REMOVE CHAIN LINK FENCING, GATE, CONDUIT, AND NON-SUPPORTING STRUCTURAL STEEL AND RECYCLE OR DISPOSE OFF-SITE AT PERMITTED SOLID WASTE DISPOSAL FACILITY.
- . REMOVE TRANSFORMER AND DISPOSE OFF—SITE AT A PERMITTED SOLID WASTE DISPOSAL FACILITY APPROVED FOR TSCA WASTES.
- COMPLETE SAW CUTS BETWEEN THE PAD AND EXISTING BUILDING WALLS (2 CUTS) AND LOADING DOCK (1 CUT).
- 6. USE IMPACT HAMMER OR JACK HAMMER TO BREAK THE TRANSFORMER PAD INTO MANAGEABLE PIECES.
- RECOVER ANY REINFORCEMENT BAR FOR RECYCLING OR OFF-SITE DISPOSAL AT A PERMITTED SOLID WASTE DISPOSAL FACILITY.
- B. DIRECT LOAD CONCRETE RUBBLE AND BLOCK INTO LINED ROLL-OFF BOX FOR TRANSPORTATION AND OFF-SITE DISPOSAL AT A TSCA APPROVED FACILITY.
- COLLECT ONE (1) GRAB SOIL SAMPLE FROM THE CENTER OF THE TRANSFORMER PAD FOOTPRINT AND ANALYZE THE SAMPLE FOR POLYCHLORINATED BIPHENYLS (1 SAMPLE PER 900 SQ. FT. REQUIRED).
- 10. TEMPORARILY COVER THE TRANSFORMER PAD FOOTPRINT WITH A TARP PENDING RECEIPT OF LABORATORY ANALYTICAL RESULTS.
- 11. IF SOIL SAMPLE TOTAL PCB CONCENTRATION EXCEEDS 50 MG/KG, REMOVE APPROXIMATELY 6 INCHES OF SOIL. RESAMPLE CENTER OF PAD FOOTPRINT SOIL FOR PCB ANALYSIS AND COVER WITH TARP.
- 12. IF SOIL GRAB SAMPLE INDICATES TOTAL PCB CONCENTRATION ABOVE 50 MG/KG, REPEAT 11 ABOVE.
 13. DISPOSE OF SOIL OFF-SITE AT A PERMITTED SOLID WASTE
- DISPOSE OF SOIL OFF-SITE AT A PERMITTED SOLID WASTE DISPOSAL FACILITY. DISPOSAL AT A LANDFILL PERMITTED TO ACCEPT TSCA WASTE MAY BE REQUIRED.
- 14. INSTALL LLDPE GEOMEMBRANE LINER AND BACKFILL TRANSFORMER PAD FOOTPRINT WITH GRAVEL TO ADJACENT GROUND SURFACE ELEVATION.



LOOKING EAST AT TRANSFORMER AND PAD LOCATED AT BUILDING NO.2.



LOOKING SOUTH AT TRANSFORMER AND PAD.



LOOKING SOUTHEAST AT TRANSFORMER, PAD AND CONCRETE BLOCK RETAINING WALL LOCATED AT BUILDING NO.2.

ISSUE DATE:



LOOKING EAST AT ELECTRIC DISTRIBUTION LINES.

REPRESENTATIVE TRANSFORMER PAD PHOTOGRAPHS

NOTE: REFER TO SPA-01 FOR LOCATION OF TRANSFORMER PAD.

PLAN PREPARER:
ALAN E. BRIGGS PROFESSIONAL ENGINEER
N.J. LICENSE NUMBER: 24GE03878500

NC. SIGNATURE DATE


CERTIFICATE OF AUTHORIZATION TO OFFER ENGINEERING SERVICES 24GA27961400


| DRWN: SCC | DATE: 04/05/09 | CHKD: RJH | DATE: 04/05/09 | APPD: JSZ | DATE: 04/05/09 | INCORPORATED


PENINSULA RESTORATION GROUP


INTERIM RESPONSE ACTION DESIGN SCCC AND DIAMOND SITES KEARNY. NEW JERSEY


TRANSFORMER PAD REMEDIATION DETAILS PROJECT NO: 09-803/804 SPA-03














REFERENCE:

AEB

AEB


APPD


1/28/10 REVISED DETAILS AND DETAIL SHEET REFERENCES

REV # DATE


ISSUED FOR BID

DESCRIPTION





TEMPORARY CONSTRUCTION TREATMENT SYSTEM (TCTS)⁽¹⁾



NOTES:

REV # DATE

- TREATMENT UNITS MAY BE MODIFIED, ENHANCED, AND/OR ELIMINATED DEPENDING ON EFFECTIVENESS OF INDIVIDUAL UNITS TO ACHIEVE PERMIT DISCHARGE LIMITS.
 MAXIMUM DAILY FLOW LESS THAN 0.1 MGD.
- FERROUS SULFATE AND SODIUM SULFIDE ADDED TO REDUCE CHROMIUM FROM THE HEXAVALENT TO TRIVALENT FORM.
- CATIONIC AND ANIONIC POLYMERS, AND/OR FLOCCULATION AID, SUCH AS FERRIC
- CHLORIDE, FOR COAGULATION AND FLOCCULATION.
 RESIDUAL-ESTIMATED AMOUNT, ACTUAL QUANTITIES MAY VARY. RESIDUALS WILL BE HANDLED AS NON-HAZARDOUS OR HAZARDOUS WASTE, DEPENDING ON CHARACTERIZATION RESULTS.

REFERENCE:

AEB

APPD

GAC TRANSPORTED OFFSITE FOR RECYCLE, REGENERATION OR DISPOSAL

ISSUED FOR BID

DESCRIPTION

= GALLONS PER MINUTE GPD GAC = GALLONS PER DAY = GRANULAR ACTIVATED CARBON DNAPL = DENSE NON-AQUEOUS PHASE LIQUID Cr VI = HEXAVALENT CHROMIUM STATE OF NEW JERSEY ERTIFICATE OF AUTHORIZATION OFFER ENGINEERING SERVICES ISSUE DATE: SIGNATURE DATE 24GA27961400

PENINSULA RESTORATION GROUP

DRWN: WAA DATE: 02/27/09 CHKD: AEB DATE: 02/27/09 APPD: PWS DATE: 02/27/09 INCORPORATED

INTERIM RESPONSE ACTION DESIGN SCCC AND DIAMOND SITES KEARNEY, NEW JERSEY

TEMPORARY TREATMENT SYSTEM LINE DRAWING

ROJECT NO: 09-803/804 TT-01

